

OIL PRODUCTS

# Diggers Anti-Mould Linseed Oil

## DESCRIPTION

**Diggers Anti-Mould Linseed Oil** is a READY-TO-USE low cost alternative to conventional decking oils - a unique product. Internal and external trials have shown this product to provide mould and mildew resistance.

## TYPICAL USES

- Natural oil for decking
- Outdoor timber sealer and protector
- Decks, fences and retaining walls

## FEATURES

- Mould, mildew and water resistant
- Ready to use – no mixing required
- Reduces the greying effect of timber
- Coverage: Softwoods/ Hardwoods: 6-8/8-10m<sup>2</sup> per litre (dependant on porosity and application technique)
- Will produce a warm, golden tone to pine and maple. Porous woods like walnut will darken considerably. Dense cabinet hardwoods will not absorb readily.

## APPLICATION

### New Timber

1. Clean surface with **Diggers Timber Cleaner**. Remove heavy deposits of wax and grease with **Diggers Wax & Grease Remover** or **Diggers Mineral Turpentine**.
2. Once dry coat with **Diggers Anti-Mould Linseed Oil**. Drying time is dependant on weather conditions but as a guideline allow approximately 24 hours between coats. Clean excess oil with a clean lint free cloth to avoid heavy build up and the surface drying sticky.

### Previously Coated/ Weathered Timber

1. Clean and remove previous coating by sanding the surface. Wash and coat as indicated above.

**How does Linseed Oil work?** *When linseed oil is applied to a porous surface it fills the pores and as it is exposed to the air it gels to form a protective film. The film is generally impervious to water, heat, scratches and most stains.*

**NOTE:** *Timber exposed to the elements will have higher absorption rate.*

**NOTE:** *Soak rags in water as spontaneous ignition may occur on drying. Dispose of rags by controlled incineration or at an approved landfill.*

## SAFETY

Wear suitable protective clothing, gloves and eye / face protection when using this product.

### Typical Characteristics

Appearance .....golden-brown  
viscous fluid  
Specific Gravity..... 0.85  
Flash Point.....typically 75°C  
Boiling Point.....190–250°C  
Flammability Limit.....0.6–7.0°C



MSDS available



Code	Pack Size	Unit Barcode	Carton Barcode	Ctn/Plt
16411-61DIG	6 x 1 litre	9312852001885	19312852001882	112
16411-4DIG	4 x 4 litre	9312852001892	19312852001899	48

#### QUEENSLAND

Tel +61 7 3308 5200  
Fax +61 7 3308 5201

#### NEW SOUTH WALES

Tel +61 2 8709 9600  
Fax +61 2 9791 5066

#### VICTORIA

Tel +61 3 9408 4144  
Fax +61 3 9408 4155

#### SOUTH AUSTRALIA

Tel +61 8 8222 1333  
Fax +61 8 8260 7883

#### WESTERN AUSTRALIA

Tel +61 8 9352 3000  
Fax +61 8 9352 3033