



SOLVENTS / PENETRANTS

Butyl Glycol Ether (BGE, EGME)

DESCRIPTION

Versatile glycol ether solvent with a high boiling point.

FEATURES

Colourless, mild smelling liquid.

Outstanding solvent power for many natural and synthetic resins, nitrocellulose and ethyl cellulose.

A starting material for chemical synthesis.

Butyl Glycol Ether is widely used in the surface coatings industry as a solvent, a viscosity improver for alkyd resins, a property regulator and a coalescer and flow improver in water-based paints.

Applied in printing inks, hydraulic fluids, household and industrial cleaners, cosmetics, agricultural formulations and cutting oils.

PACKAGING

Butyl Glycol Ether is available in drums.

SAFETY

Please consult the MSDS on **Butyl Glycol Ether** before use.

The information and recommendations contained herein are based on data believed to be correct at this time. However, no guarantee of any kind, expressed or implied is made with respect to the information contained herein.

Typical Characteristics

Molecular Weight (g/mole)	118.2
Boiling Point	171°C
Flash Point	67°C
Specific Gravity	0.898
Net Heat Of Combustion (J/g)	
– predicted @ 25°C	30.0
Solubility, g/100g @ 25°C	
Solvent In Water	∞
Water in Solvent	∞



MSDS available

QUEENSLAND
Tel +61 7 3308 5200
Fax +61 7 3308 5201

NEW SOUTH WALES
Tel +61 2 8709 9600
Fax +61 2 9791 5066

VICTORIA
Tel +61 3 9408 4144
Fax +61 3 9408 4155

SOUTH AUSTRALIA
Tel +61 8 8222 1333
Fax +61 8 8260 7883

WESTERN AUSTRALIA
Tel +61 8 9352 3000
Fax +61 8 9352 3033