



SOLVENTS / PENETRANTS

Cyclohexanone

DESCRIPTION

Cyclic ketone primarily used in nylon production, coatings and penetrating oil formulations.

FEATURES

Good solvency in both hydrocarbons and chemical solvents.

Strong penetrating abilities in all purpose lubricants.

Slow to medium evaporation rate.

Minimum residue on drying.

The precursor to Nylon 6 and Nylon 66 production.

Solvency – Cyclohexanone is miscible with most organic solvents.

Versatility – Cyclohexanone can be included in many coating formulations where controlled evaporation is required.

PACKAGING

Cyclohexanone is available in drums.

SAFETY

Please consult the MSDS on Cyclohexanone before use.

The information and recommendations contained herein are based on data believed to be correct at this time. However, no guarantee of any kind, expressed or implied is made with respect to the information contained herein.

Typical Characteristics

Appearance	clear liquid
Flash Point.....	45°C
Boiling Range	153–158°C
Specific Gravity.....	0.948



MSDS available

QUEENSLAND
Tel +61 7 3308 5200
Fax +61 7 3308 5201

NEW SOUTH WALES
Tel +61 2 8709 9600
Fax +61 2 9791 5066

VICTORIA
Tel +61 3 9408 4144
Fax +61 3 9408 4155

SOUTH AUSTRALIA
Tel +61 8 8222 1333
Fax +61 8 8260 7883

WESTERN AUSTRALIA
Tel +61 8 9352 3000
Fax +61 8 9352 3033