



SOLVENTS / PENETRANTS

# Cyclohexanone

## DESCRIPTION

Cyclic ketone primarily used in nylon production, coatings and penetrating oil formulations.

## FEATURES

Good solvency in both hydrocarbons and chemical solvents.

Strong penetrating abilities in all purpose lubricants.

Slow to medium evaporation rate.

Minimum residue on drying.

The precursor to Nylon 6 and Nylon 66 production.

**Solvency** – Cyclohexanone is miscible with most organic solvents.

**Versatility** – Cyclohexanone can be included in many coating formulations where controlled evaporation is required.

## PACKAGING

Cyclohexanone is available in drums.

## SAFETY

Please consult the MSDS on Cyclohexanone before use.

The information and recommendations contained herein are based on data believed to be correct at this time. However, no guarantee of any kind, expressed or implied is made with respect to the information contained herein.

### Typical Characteristics

Appearance .....	clear liquid
Flash Point.....	45°C
Boiling Range .....	153–158°C
Specific Gravity.....	0.948



MSDS available

QUEENSLAND  
Tel +61 7 3308 5200  
Fax +61 7 3308 5201

NEW SOUTH WALES  
Tel +61 2 8709 9600  
Fax +61 2 9791 5066

VICTORIA  
Tel +61 3 9408 4144  
Fax +61 3 9408 4155

SOUTH AUSTRALIA  
Tel +61 8 8222 1333  
Fax +61 8 8260 7883

WESTERN AUSTRALIA  
Tel +61 8 9352 3000  
Fax +61 8 9352 3033