



SOLVENTS / PENETRANTS

Heptane

DESCRIPTION

A highly refined and hydrotreated petroleum heptane solvent with fast-to-medium evaporating aliphatics.

FEATURES

Narrow boiling range gives the solvent a well regulated drying performance.

Low odour.

Used in both printing and laboratory applications.

Used as a solvent and diluent in quick drying lacquers, paints, varnishes and inks.

In the grease spot test, **Heptane** is used to dissolve the oil spot to show the previous presence of organic compounds on a stained paper.

PACKAGING

Heptane is available in drums.

SAFETY

Please consult the MSDS on **Heptane** before use.

The information and recommendations contained herein are based on data believed to be correct at this time. However, no guarantee of any kind, expressed or implied is made with respect to the information contained herein.

Typical Characteristics

Appearance	colourless liquid
Melting Point.....	-91°C
Boiling Range	90-100°C
Specific Gravity.....	0.70-0.71
Flash Point.....	-5°C



MSDS available

QUEENSLAND
Tel +61 7 3308 5200
Fax +61 7 3308 5201

NEW SOUTH WALES
Tel +61 2 8709 9600
Fax +61 2 9791 5066

VICTORIA
Tel +61 3 9408 4144
Fax +61 3 9408 4155

SOUTH AUSTRALIA
Tel +61 8 8222 1333
Fax +61 8 8260 7883

WESTERN AUSTRALIA
Tel +61 8 9352 3000
Fax +61 8 9352 3033