



## SOLVENTS / PENETRANTS

# Heptane

### DESCRIPTION

A highly refined and hydrotreated petroleum heptane solvent with fast-to-medium evaporating aliphatics.

### FEATURES

Narrow boiling range gives the solvent a well regulated drying performance.

Low odour.

Used in both printing and laboratory applications.

Used as a solvent and diluent in quick drying lacquers, paints, varnishes and inks.

In the grease spot test, **Heptane** is used to dissolve the oil spot to show the previous presence of organic compounds on a stained paper.

### PACKAGING

**Heptane** is available in drums.

### SAFETY

Please consult the MSDS on **Heptane** before use.

The information and recommendations contained herein are based on data believed to be correct at this time. However, no guarantee of any kind, expressed or implied is made with respect to the information contained herein.

### Typical Characteristics

Appearance .....	colourless liquid
Melting Point.....	-91°C
Boiling Range .....	90-100°C
Specific Gravity.....	0.70-0.71
Flash Point.....	-5°C



**MSDS** available

**QUEENSLAND**  
Tel +61 7 3308 5200  
Fax +61 7 3308 5201

**NEW SOUTH WALES**  
Tel +61 2 8709 9600  
Fax +61 2 9791 5066

**VICTORIA**  
Tel +61 3 9408 4144  
Fax +61 3 9408 4155

**SOUTH AUSTRALIA**  
Tel +61 8 8222 1333  
Fax +61 8 8260 7883

**WESTERN AUSTRALIA**  
Tel +61 8 9352 3000  
Fax +61 8 9352 3033