



SOLVENTS / PENETRANTS

# Isohexane

## DESCRIPTION

A clear, colourless liquid commonly used as a constituent of gasoline and glues used for shoes, leather products and roofing. Additionally, it is used in solvents to extract oils for cooking and as a cleansing agent for shoe, furniture and textile manufacturing. In laboratories, **Isohexane** is used to extract oil and grease from water and soil before determination by gravimetric analysis or gas chromatography.

## FEATURES

Alternative to n-Hexane.

Can be used in brake cleaners, adhesives and as a polymerisation solvent.

## PACKAGING

**Isohexane** is available in drums.

## SAFETY

Please consult the MSDS on **Isohexane** before use.

The information and recommendations contained herein are based on data believed to be correct at this time. However, no guarantee of any kind, expressed or implied is made with respect to the information contained herein.

### Typical Characteristics

Appearance .....	colourless liquid
Melting Point.....	-154°C
Boiling Point.....	56–63°C
Specific Gravity.....	0.653
Flash Point (closed cup) .....	-7°C
n-Hexane Content .....	5% max



**MSDS** available

**QUEENSLAND**  
Tel +61 7 3308 5200  
Fax +61 7 3308 5201

**NEW SOUTH WALES**  
Tel +61 2 8709 9600  
Fax +61 2 9791 5066

**VICTORIA**  
Tel +61 3 9408 4144  
Fax +61 3 9408 4155

**SOUTH AUSTRALIA**  
Tel +61 8 8222 1333  
Fax +61 8 8260 7883

**WESTERN AUSTRALIA**  
Tel +61 8 9352 3000  
Fax +61 8 9352 3033