



SOLVENTS / PENETRANTS

Isohexane

DESCRIPTION

A clear, colourless liquid commonly used as a constituent of gasoline and glues used for shoes, leather products and roofing. Additionally, it is used in solvents to extract oils for cooking and as a cleansing agent for shoe, furniture and textile manufacturing. In laboratories, **Isohexane** is used to extract oil and grease from water and soil before determination by gravimetric analysis or gas chromatography.

FEATURES

Alternative to n-Hexane.

Can be used in brake cleaners, adhesives and as a polymerisation solvent.

PACKAGING

Isohexane is available in drums.

SAFETY

Please consult the MSDS on **Isohexane** before use.

The information and recommendations contained herein are based on data believed to be correct at this time. However, no guarantee of any kind, expressed or implied is made with respect to the information contained herein.

Typical Characteristics

Appearance	colourless liquid
Melting Point.....	-154°C
Boiling Point.....	56–63°C
Specific Gravity.....	0.653
Flash Point (closed cup)	-7°C
n-Hexane Content	5% max



MSDS available

QUEENSLAND
Tel +61 7 3308 5200
Fax +61 7 3308 5201

NEW SOUTH WALES
Tel +61 2 8709 9600
Fax +61 2 9791 5066

VICTORIA
Tel +61 3 9408 4144
Fax +61 3 9408 4155

SOUTH AUSTRALIA
Tel +61 8 8222 1333
Fax +61 8 8260 7883

WESTERN AUSTRALIA
Tel +61 8 9352 3000
Fax +61 8 9352 3033