



## SOLVENTS / PENETRANTS

# MEK (Methyl Ethyl Ketone)

### DESCRIPTION

A low flash point, oxygenated solvent with a characteristic odour. **MEK** is a versatile, inexpensive, work-horse Ketone suitable for acrylic coating formulations, as a clean-up solvent for polymeric manufacturing and in specialty chemical formulations.

### FEATURES

A flammable solvent soluble in alcohol and hydrocarbons.

Widely available with extensive on-hand information.

**Solubility** – **MEK** is soluble in polar and non-polar organic materials making it an ideal component in coatings, thinners and reducer formulations. **MEK** will effect a slower evaporation rate for a premium gloss finish.

### PACKAGING

**MEK** is available in drums and 20 litre containers.

### SAFETY

Please consult the MSDS on **MEK** before use.

The information and recommendations contained herein are based on data believed to be correct at this time. However, no guarantee of any kind, expressed or implied is made with respect to the information contained herein.

### Typical Characteristics

Appearance .....	clear, colourless liquid
Odour.....	acetone-like, pungent
Specific Gravity.....	0.806
Flash Point.....	-4°C
Boiling Point.....	78°C
Percent Volatiles .....	100%
Molecular Weight .....	72.12g/mole



**MSDS** available

**QUEENSLAND**  
Tel +61 7 3308 5200  
Fax +61 7 3308 5201

**NEW SOUTH WALES**  
Tel +61 2 8709 9600  
Fax +61 2 9791 5066

**VICTORIA**  
Tel +61 3 9408 4144  
Fax +61 3 9408 4155

**SOUTH AUSTRALIA**  
Tel +61 8 8222 1333  
Fax +61 8 8260 7883

**WESTERN AUSTRALIA**  
Tel +61 8 9352 3000  
Fax +61 8 9352 3033