



ALCOHOLS (NON-ETHANOL)

Methanol

DESCRIPTION

The simplest alcohol widely used in the oil and gas industries to help absorb hydrates in natural gas production. It is an integral component in the manufacture of biodiesel and is commonly used as a speedway fuel in motor racing.

FEATURES

A low flash point solvent with a high evaporation rate.

An excellent solvent for most natural and synthetic resins.

A high purity fuel with low viscosity.

Absorbs moisture readily which assists in natural gas drying.

Versatility – **Methanol** can be included in any formulation where speed of evaporation is required and it combines well with other organic compounds.

Solvency – **Methanol** has high solvency of resins used in surface coatings or as a specialised fuel.

PACKAGING

Methanol is available in IBCs (1500 litre stainless steel bulk containers), drums and 20 litre containers.

SAFETY

Please consult the MSDS on **Methanol** before use.

The information and recommendations contained herein are based on data believed to be correct at this time. However, no guarantee of any kind, expressed or implied is made with respect to the information contained herein.

Typical Characteristics

Specific Gravity.....	0.790–0.796
Flash Point.....	11°C
Boiling Range	64.5–64.6 °C
Acidity [as Acetic Acid] wt	0.003
Purity	99.8% min



MSDS available

QUEENSLAND
Tel +61 7 3308 5200
Fax +61 7 3308 5201

NEW SOUTH WALES
Tel +61 2 8709 9600
Fax +61 2 9791 5066

VICTORIA
Tel +61 3 9408 4144
Fax +61 3 9408 4155

SOUTH AUSTRALIA
Tel +61 8 8222 1333
Fax +61 8 8260 7883

WESTERN AUSTRALIA
Tel +61 8 9352 3000
Fax +61 8 9352 3033