



SOLVENTS / PENETRANTS

# Recosol 165

## DESCRIPTION

High flash solvent blend that performs well in situations requiring a high level of solvency such as cleaning difficult oil and grease residues from pipe work, including oilfield wells.

## FEATURES

High flash point.

Not classified as dangerous goods for transport or storage.

High solvency product that is effective on stubborn grease and oil residues.

Soluble in water.

**Versatility** – **Recosol 165** can be included in any formulation where boosted solvency power is required and will combine well with other organic compounds.

**Solvency** – **Recosol 165** has high solvency of greases, oils and general dirt as well as polymeric surface coatings and specific use branched chain, high molecular weight organics.

## PACKAGING

**Recosol 165** is available in IBCs (1000 litre bulk containers) and drums.

## SAFETY

Please consult the MSDS on **Recosol 165** before use.

The information and recommendations contained herein are based on data believed to be correct at this time. However, no guarantee of any kind, expressed or implied is made with respect to the information contained herein.

### Typical Characteristics

Specific Gravity.....	0.89
Flash Point.....	65°C
Boiling Range .....	172-210°C
Aromatic Content.....	90%



MSDS available

QUEENSLAND  
Tel +61 7 3308 5200  
Fax +61 7 3308 5201

NEW SOUTH WALES  
Tel +61 2 8709 9600  
Fax +61 2 9791 5066

VICTORIA  
Tel +61 3 9408 4144  
Fax +61 3 9408 4155

SOUTH AUSTRALIA  
Tel +61 8 8222 1333  
Fax +61 8 8260 7883

WESTERN AUSTRALIA  
Tel +61 8 9352 3000  
Fax +61 8 9352 3033