



SOLVENTS / PENETRANTS

Recosol 30B

DESCRIPTION

A low flash point, 50% aromatic hydrocarbon solvent that performs well in situations requiring a high level of solvency such as enamel paint formulations.

FEATURES

A narrow boiling range solvent with a medium evaporation rate.

Leaves no residue upon drying.

A high solvency product that is effective on complex resin systems and used extensively in paint formulations.

Strong wax and grease remover.

Versatility – **Recosol 30B** can be included in any formulation where boosted solvency power is required and will combine well with other organic compounds.

Solvency – **Recosol 30B** has high solvency of greases, oils and general dirt as well as sophisticated polymeric surface coatings and specific use, branched-chain, high molecular weight organics.

PACKAGING

Recosol 30B is available in bulk, IBCs (1500 litre bulk containers), drums and 20 litre containers.

SAFETY

Please consult the MSDS on **Recosol 30B** before use.

The information and recommendations contained herein are based on data believed to be correct at this time. However, no guarantee of any kind, expressed or implied is made with respect to the information contained herein.

Typical Characteristics

Specific Gravity.....	0.802
Flash Point.....	<0°C
Boiling Range	106-134°C
Aromatic Content.....	50%

 **MSDS** available

QUEENSLAND
Tel +61 7 3308 5200
Fax +61 7 3308 5201

NEW SOUTH WALES
Tel +61 2 8709 9600
Fax +61 2 9791 5066

VICTORIA
Tel +61 3 9408 4144
Fax +61 3 9408 4155

SOUTH AUSTRALIA
Tel +61 8 8222 1333
Fax +61 8 8260 7883

WESTERN AUSTRALIA
Tel +61 8 9352 3000
Fax +61 8 9352 3033