



SOLVENTS / PENETRANTS

Recosol 80/100

DESCRIPTION

A highly refined petroleum solvent specifically developed for the preparation of metallic surfaces prior to painting and in particular powder coatings. **Recosol 80/100** removes most surface contaminants easily and evaporates very quickly after cleaning.

FEATURES

A clear and bright fluid which leaves no stains, residue or lasting odour.

A high purity product which contains almost no aromatics.

High Purity – **Recosol 80/100** is a narrow boiling range solvent. It does not contain any appreciable levels of aromatic compounds, rendering surfaces clean and dry in a short time.

Odour and Colour – **Recosol 80/100** is water white and has a mild odour, especially in comparison with other solvents traditionally used for surface preparation prior to painting.

PACKAGING

Recosol 80/100 is available in drums.

SAFETY

Please consult the MSDS on **Recosol 80/100** before use.

The information and recommendations contained herein are based on data believed to be correct at this time. However, no guarantee of any kind, expressed or implied is made with respect to the information contained herein.

Typical Characteristics

Specific Gravity.....	0.716
Flash Point (open cup).....	-9°C
Boiling Range	79-96°C
Percent Volatiles	100%
Aromatics.....	0.05%



MSDS available

QUEENSLAND
Tel +61 7 3308 5200
Fax +61 7 3308 5201

NEW SOUTH WALES
Tel +61 2 8709 9600
Fax +61 2 9791 5066

VICTORIA
Tel +61 3 9408 4144
Fax +61 3 9408 4155

SOUTH AUSTRALIA
Tel +61 8 8222 1333
Fax +61 8 8260 7883

WESTERN AUSTRALIA
Tel +61 8 9352 3000
Fax +61 8 9352 3033