



## SOLVENTS / PENETRANTS

# Recosol 98

### DESCRIPTION

Specialty paraffinic fluid used in many applications, including as a coolant in spark erosion machines, a rolling oil for most metals and as a base oil in polymer emulsions.

### FEATURES

Premium grade paraffinic fluid.

A clear, water white fluid with low volatility.

A highly refined product with low odour and reactivity.

Burns cleanly and is ideal for low odour lamp oil formulations.

Can provide thin film lubrication and good penetration as a rolling oil.

**Highly Refined - Recosol 98** is chemically stable and is non-regulated for storage and handling.

**Safety - Recosol 98** is considered non-toxic and can be used in applications whereby direct contact with food and beverages is likely to eventuate.

### PACKAGING

**Recosol 98** is available in drums and 20 litre containers.

### SAFETY

Please consult the MSDS on **Recosol 98** before use.

The information and recommendations contained herein are based on data believed to be correct at this time. However, no guarantee of any kind, expressed or implied is made with respect to the information contained herein.

### Typical Characteristics

Specific Gravity.....	0.75
Flash Point (open cup).....	95°C
Appearance .....	clear liquid
Boiling Range .....	215-235°C
Kinematic Viscosity @ 40°C .....	2.0 cSt



MSDS available

QUEENSLAND  
Tel +61 7 3308 5200  
Fax +61 7 3308 5201

NEW SOUTH WALES  
Tel +61 2 8709 9600  
Fax +61 2 9791 5066

VICTORIA  
Tel +61 3 9408 4144  
Fax +61 3 9408 4155

SOUTH AUSTRALIA  
Tel +61 8 8222 1333  
Fax +61 8 8260 7883

WESTERN AUSTRALIA  
Tel +61 8 9352 3000  
Fax +61 8 9352 3033