



SOLVENTS / PENETRANTS – LOW ODOUR

# Recosol GT

## DESCRIPTION

100% Isoparaffinic fluid used in surface coating formulations, lamp oils and roof sheeting rolling oil applications.

## FEATURES

A very low odour solvent that is a convenient alternative to Mineral Turpentine, White Spirits or Kerosene.

Use when an 'odourless' solvent is required.

Low aromatic content ensures lower potential for attack of plastics and rubbers.

Can be used as a rolling oil for Colorbond™ and aluminium roofing sheets.

**Versatility** – Recosol GT can be substituted for many traditional solvents in cleaning formulations as well as sophisticated blends requiring a low odour.

**Selective Solvency** – Recosol GT has a high solvency of greases, oils and general dirt, but does not have the inherent capability to swell rubbers or plastics. This makes it an appropriate electrical cleaner which can be stored in containers with low tolerance seals.

## PACKAGING

Recosol GT is available in drums and 20 litre containers.

## SAFETY

Please consult the MSDS on **Recosol GT** before use.

The information and recommendations contained herein are based on data believed to be correct at this time. However, no guarantee of any kind, expressed or implied is made with respect to the information contained herein.

### Typical Characteristics

Specific Gravity.....	0.745
Flash Point.....	41°C
Boiling Range .....	155–175°C
Aromatic Content.....	<100ppm
Aniline Point.....	78°C



MSDS available

**QUEENSLAND**  
Tel +61 7 3308 5200  
Fax +61 7 3308 5201

**NEW SOUTH WALES**  
Tel +61 2 8709 9600  
Fax +61 2 9791 5066

**VICTORIA**  
Tel +61 3 9408 4144  
Fax +61 3 9408 4155

**SOUTH AUSTRALIA**  
Tel +61 8 8222 1333  
Fax +61 8 8260 7883

**WESTERN AUSTRALIA**  
Tel +61 8 9352 3000  
Fax +61 8 9352 3033