



SOLVENTS / PENETRANTS – LOW ODOUR

Recosol GT

DESCRIPTION

100% Isoparaffinic fluid used in surface coating formulations, lamp oils and roof sheeting rolling oil applications.

FEATURES

A very low odour solvent that is a convenient alternative to Mineral Turpentine, White Spirits or Kerosene.

Use when an 'odourless' solvent is required.

Low aromatic content ensures lower potential for attack of plastics and rubbers.

Can be used as a rolling oil for Colorbond™ and aluminium roofing sheets.

Versatility – Recosol GT can be substituted for many traditional solvents in cleaning formulations as well as sophisticated blends requiring a low odour.

Selective Solvency – Recosol GT has a high solvency of greases, oils and general dirt, but does not have the inherent capability to swell rubbers or plastics. This makes it an appropriate electrical cleaner which can be stored in containers with low tolerance seals.

PACKAGING

Recosol GT is available in drums and 20 litre containers.

SAFETY

Please consult the MSDS on **Recosol GT** before use.

The information and recommendations contained herein are based on data believed to be correct at this time. However, no guarantee of any kind, expressed or implied is made with respect to the information contained herein.

Typical Characteristics

Specific Gravity.....	0.745
Flash Point.....	41°C
Boiling Range	155–175°C
Aromatic Content.....	<100ppm
Aniline Point.....	78°C



MSDS available

QUEENSLAND
Tel +61 7 3308 5200
Fax +61 7 3308 5201

NEW SOUTH WALES
Tel +61 2 8709 9600
Fax +61 2 9791 5066

VICTORIA
Tel +61 3 9408 4144
Fax +61 3 9408 4155

SOUTH AUSTRALIA
Tel +61 8 8222 1333
Fax +61 8 8260 7883

WESTERN AUSTRALIA
Tel +61 8 9352 3000
Fax +61 8 9352 3033