



SOLVENTS / PENETRANTS

Recosol R55 (Shellite)

DESCRIPTION

A highly volatile hydrocarbon solvent that performs well in situations requiring a solvent that evaporates quickly with no residue.

FEATURES

Fast drying.

Can be used as a low residue contact cleaner.

A low flash point solvent that evaporates quickly.

A weak solvent that is unlikely to affect the surface of most materials.

Versatility – **Recosol R55** can be included in any formulation where speed of evaporation is required and will combine well with other organic compounds.

Solvency – **Recosol R55** has high solvency of greases and oils. It can be used to clean surfaces prior to painting.

PACKAGING

Recosol R55 is available in IBCs (1500 litre bulk containers), drums and 20 litre containers.

SAFETY

Please consult the MSDS on **Recosol R55** before use.

The information and recommendations contained herein are based on data believed to be correct at this time. However, no guarantee of any kind, expressed or implied is made with respect to the information contained herein.

Typical Characteristics

Specific Gravity.....	0.67–0.70
Flash Point.....	<0°C
Boiling Range	50–135°C
Paraffins Content	75%
Naphthenes Content.....	22%
Aromatic Content.....	3%



MSDS available

QUEENSLAND
Tel +61 7 3308 5200
Fax +61 7 3308 5201

NEW SOUTH WALES
Tel +61 2 8709 9600
Fax +61 2 9791 5066

VICTORIA
Tel +61 3 9408 4144
Fax +61 3 9408 4155

SOUTH AUSTRALIA
Tel +61 8 8222 1333
Fax +61 8 8260 7883

WESTERN AUSTRALIA
Tel +61 8 9352 3000
Fax +61 8 9352 3033

© Copyright Recochem Inc. All rights reserved. All content remains the property of Recochem Inc. All other trademarks mentioned are trademarks or registered trademarks of their respective owners. All text, images, graphics and PDF files are subject to the copyrights and intellectual property rights of Recochem Inc. Separate to the purpose of review and private use, this information cannot be used without written permission from Recochem. Information contained herein is for general information only and should not be used as an infallible to a product's specification and or performance.