



SOLVENTS / PENETRANTS

Recosol Wax & Grease Remover

DESCRIPTION

A wide boiling range, low aromatic, aliphatic cleaning solvent.

FEATURES

A low flash point solvent which leaves no residue on drying.

Immiscible with water.

Provides exceptional performance as a preparation solvent in the automotive refinish industry.

Solvency – **Recosol Wax & Grease Remover** has high solvency for greases, oils and silicones making it ideal for cleaning surfaces prior to painting.

Low Odour – **Recosol Wax & Grease Remover** has a lower aromatic content than other cleaning solvents making it more pleasant to use than high aromatic products. The low aromatic content also reduces potential for skin irritation.

PACKAGING

Recosol Wax & Grease Remover is available in IBCs (1500 litre bulk containers), drums and 20 litre containers.

SAFETY

Please consult the MSDS on **Recosol Wax & Grease Remover** before use.

The information and recommendations contained herein are based on data believed to be correct at this time. However, no guarantee of any kind, expressed or implied is made with respect to the information contained herein.

Typical Characteristics

Specific Gravity.....	0.764
Flash Point.....	<-30°C
Boiling Range	47–200°C
Percent Volatiles	100%

 **MSDS** available

QUEENSLAND
Tel +61 7 3308 5200
Fax +61 7 3308 5201

NEW SOUTH WALES
Tel +61 2 8709 9600
Fax +61 2 9791 5066

VICTORIA
Tel +61 3 9408 4144
Fax +61 3 9408 4155

SOUTH AUSTRALIA
Tel +61 8 8222 1333
Fax +61 8 8260 7883

WESTERN AUSTRALIA
Tel +61 8 9352 3000
Fax +61 8 9352 3033