



SOLVENTS / PENETRANTS

Recosol X95

DESCRIPTION

Recosol X95 is a wide boiling range, medium evaporating solvent widely used in the production of resins. **Recosol X95** is an aliphatic solvent with properties between Recosol R55 (faster) and White Spirits (slower), but with similar solvency. It evaporates quickly leaving no residue.

FEATURES

Low flash point solvent with a medium evaporation rate.

High solvency of grease, oil and silicones without attacking cured coatings.

Aliphatic odour.

Miscible with other organic solvents; not miscible with water.

Recosol X95 can be included in any formulation where controlled evaporation speed is required.

Suitable for special applications such as cleaning electrical components, brakes and hydraulic lines.

PACKAGING

Recosol X95 is available in drums and 20 litre containers.

SAFETY

Please consult the MSDS on **Recosol X95** before use.

The information and recommendations contained herein are based on data believed to be correct at this time. However, no guarantee of any kind, expressed or implied is made with respect to the information contained herein.

Typical Characteristics

Appearance	clear liquid
Specific Gravity.....	0.7-0.77
Flash Point.....	min -6°C
Boiling Range	90–140°C



MSDS available

QUEENSLAND
Tel +61 7 3308 5200
Fax +61 7 3308 5201

NEW SOUTH WALES
Tel +61 2 8709 9600
Fax +61 2 9791 5066

VICTORIA
Tel +61 3 9408 4144
Fax +61 3 9408 4155

SOUTH AUSTRALIA
Tel +61 8 8222 1333
Fax +61 8 8260 7883

WESTERN AUSTRALIA
Tel +61 8 9352 3000
Fax +61 8 9352 3033

© Copyright Recochem Inc. All rights reserved. All content remains the property of Recochem Inc. All other trademarks mentioned are trademarks or registered trademarks of their respective owners. All text, images, graphics and PDF files are subject to the copyrights and intellectual property rights of Recochem Inc. Separate to the purpose of review and private use, this information cannot be used without written permission from Recochem. Information contained herein is for general information only and should not be used as an infallible to a product's specification and or performance.