



SOLVENTS / PENETRANTS

Toluene

DESCRIPTION

Aromatic hydrocarbon solvent that performs well in situations requiring a high level of solvency. **Toluene** is common in many coating formulations, including acrylic thinners and 2 pack epoxies.

FEATURES

Removing carpet and vinyl glue.

Used in chemical manufacturing.

Fast evaporating solvent.

Colourless liquid with a characteristic odour.

Solvency – Toluene can be included in any formulation where boosted solvency power is required and will combine well with other organic compounds. It has a very high solvency of greases, oils and general dirt as well as sophisticated polymeric surface coatings and specific high molecular-weight organics.

PACKAGING

Toluene is available in bulk, IBCs (1500 litre bulk containers), drums, 20 litre containers and 4 x4 litre and 6 x 1 litre cartons.

SAFETY

Please consult the MSDS on **Toluene** before use.

The information and recommendations contained herein are based on data believed to be correct at this time. However, no guarantee of any kind, expressed or implied is made with respect to the information contained herein.

Typical Characteristics

Appearance	colourless liquid
Specific Gravity.....	0.871
Flash Point.....	4°C
Boiling Point.....	110–111°C
Flammability Limit.....	1.2–8%
Auto Ignition Temperature.....	480–536°C



MSDS available

QUEENSLAND
Tel +61 7 3308 5200
Fax +61 7 3308 5201

NEW SOUTH WALES
Tel +61 2 8709 9600
Fax +61 2 9791 5066

VICTORIA
Tel +61 3 9408 4144
Fax +61 3 9408 4155

SOUTH AUSTRALIA
Tel +61 8 8222 1333
Fax +61 8 8260 7883

WESTERN AUSTRALIA
Tel +61 8 9352 3000
Fax +61 8 9352 3033