



SOLVENTS / PENETRANTS

Xylene Solvent Grade

DESCRIPTION

An aromatic hydrocarbon solvent that performs well in situations requiring a high level of solvency. Xylene is common to many coating formulations, including general industrial enamels, 2 pack epoxies and polyurethanes. **Xylene Solvent Grade** is similar to normal Xylene, it contains three isomers of xylene and also ethylbenzene.

FEATURES

High solvency.

Mid range evaporation rate.

A widely available and used solvent for specialised uses in the chemical industry.

Versatility – **Xylene Solvent Grade** can be included in any formulation where boosted solvency power is required and will combine well with other organic compounds.

Solvency – **Xylene Solvent Grade** has high solvency of greases, oils and general dirt as well as sophisticated polymeric surface coatings and specific high molecular-weight organics.

PACKAGING

Xylene Solvent Grade is available in drums.

SAFETY

Please consult the MSDS on **Xylene Solvent Grade** before use.

The information and recommendations contained herein are based on data believed to be correct at this time. However, no guarantee of any kind, expressed or implied is made with respect to the information contained herein.

Typical Characteristics

Appearance	colourless liquid
Specific Gravity.....	0.86-0.87
Flash Point.....	27°C
Boiling Range	137–143°C
Flammability Limit.....	1–7%
Auto Ignition Temperature.....	>450°C



MSDS available

QUEENSLAND
Tel +61 7 3308 5200
Fax +61 7 3308 5201

NEW SOUTH WALES
Tel +61 2 8709 9600
Fax +61 2 9791 5066

VICTORIA
Tel +61 3 9408 4144
Fax +61 3 9408 4155

SOUTH AUSTRALIA
Tel +61 8 8222 1333
Fax +61 8 8260 7883

WESTERN AUSTRALIA
Tel +61 8 9352 3000
Fax +61 8 9352 3033