



SOLVENTS / PENETRANTS

n-Butyl Acetate

DESCRIPTION

Widely used ester in the surface coatings industry. Specific areas of use include 2-pack polyurethanes, wood coatings, acid curing and single-pack lacquers.

FEATURES

Relatively fast evaporation rate (has the benchmark rate of 1).

Good solvency in hydrocarbons and resins.

Fruity odour.

Versatility – n-Butyl Acetate can be included in a wide variety of thinners and coatings.

Solvency – n-Butyl Acetate has good compatibility with most other solvents used in thinner formulations.

PACKAGING

n-Butyl Acetate is available in drums.

SAFETY

Please consult the MSDS on n-Butyl Acetate before use.

The information and recommendations contained herein are based on data believed to be correct at this time. However, no guarantee of any kind, expressed or implied is made with respect to the information contained herein.

Typical Characteristics

Appearanceclear, bright liquid
Specific Gravity.....0.882
Flash Point.....23°C
Boiling Range 124–128°C



MSDS available

QUEENSLAND
Tel +61 7 3308 5200
Fax +61 7 3308 5201

NEW SOUTH WALES
Tel +61 2 8709 9600
Fax +61 2 9791 5066

VICTORIA
Tel +61 3 9408 4144
Fax +61 3 9408 4155

SOUTH AUSTRALIA
Tel +61 8 8222 1333
Fax +61 8 8260 7883

WESTERN AUSTRALIA
Tel +61 8 9352 3000
Fax +61 8 9352 3033