



## ALCOHOLS (NON-ETHANOL)

# n-Propanol

### DESCRIPTION

A straight-chain alcohol for use in the surface coatings industry. Specifically it can be used in flexographic printing and the pharmaceutical industry.

### FEATURES

Fast evaporation rate.

Mild alcohol odour.

Miscible with water.

**Versatility** – n-Propanol can be used in a variety of surface coating applications.

### PACKAGING

n-Propanol is available in drums.

### SAFETY

Please consult the MSDS on n-Propanol before use.

The information and recommendations contained herein are based on data believed to be correct at this time. However, no guarantee of any kind, expressed or implied is made with respect to the information contained herein.

### Typical Characteristics

Appearance .....	clear, water-white liquid
Odour.....	mild alcohol odour (detectable at 30-40 ppm)
Boiling Point.....	97°C
Melting Point.....	-126.5°C
Vapour Pressure.....	14.5 mm Hg @ 20°C
Specific Gravity.....	0.803
Solubility In Water.....	100% by weight
Evaporation Rate.....	220 (n-Butyl = acetate100)
Vapour Density .....	2.1 (air = 1)
Percent Volatiles .....	100%
Flash Point.....	22°C
Lower Explosive Limit (LEL) .....	2.1%
Upper Explosive Limit (UEL) .....	13.7%

 MSDS available

QUEENSLAND  
Tel +61 7 3308 5200  
Fax +61 7 3308 5201

NEW SOUTH WALES  
Tel +61 2 8709 9600  
Fax +61 2 9791 5066

VICTORIA  
Tel +61 3 9408 4144  
Fax +61 3 9408 4155

SOUTH AUSTRALIA  
Tel +61 8 8222 1333  
Fax +61 8 8260 7883

WESTERN AUSTRALIA  
Tel +61 8 9352 3000  
Fax +61 8 9352 3033