



MATERIAL SAFETY DATA SHEET

SECTION 1 IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name: LINSEED OIL WITH ANTI-MOULD READY TO USE

Company: Recochem Inc. ABN: 69 010 485 999
Address : 1809 Lytton Road, Lytton, Queensland 4178
Phone: (07) 3308 5200 Fax: (07) 3308 5201
Emergency Telephone Number: (07) 3308 5200 Day, After Hours 1300 131 001

Other Names: Blended Linseed Oil
Manufacturer's Product Code: 16411
Recommended Use: Preservation of timber and timber products

SECTION 2 HAZARDS IDENTIFICATION

**CLASSIFIED AS HAZARDOUS ACCORDING TO CRITERIA OF WORKSAFE AUSTRALIA
NOT A DANGEROUS GOODS ACCORDING TO THE CRITERIA OF THE ADG CODE**

Symbols: Xn - Harmful
Xi - Irritant
N - Dangerous for the environment

Risk Phrases: R43 - May cause sensitisation by skin contact
R50 - Very toxic to aquatic organisms
R53 - May cause long term adverse effects in the aquatic environment
R65 - Harmful: May cause lung damage if swallowed

Safety Phrases: S1/2 - Keep locked and out of the reach of children
S23 - Do not breathe vapour
S24 - Avoid contact with skin
S26 - In case of contact with eyes, rinse immediately with plenty of water and seek medical advice
S36/37/39 - Wear suitable protective clothing, gloves and eye/face protection
S45 - In case of accident or if you feel unwell, seek medical advice immediately (show label where possible)
S60 - This material and its container must be disposed of as hazardous waste
S61 - Avoid release to the environment. Refer to special instructions/safety data sheets
S62 - If swallowed, do not induce vomiting: seek medical advice immediately and show container or label

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

INGREDIENTS

<i>Chemical Entity</i>	<i>CAS Number</i>	<i>Proportion (%)</i>
Boiled Linseed Oil	8001-26-1	30 - 50
Kerosene (petroleum), hydrosulphurised	64742-81-0	50 - 70
2-Octyl-2H-isothiazol-3-one	26530-20-1	< 1

SECTION 4 FIRST AID MEASURES

FIRST AID TREATMENT

Swallowed: If swallowed, do NOT induce vomiting. Transport to nearest medical facility for additional treatment. If vomiting occurs spontaneously, keep head below hips to prevent aspiration.

Eye: If in eyes, hold eyes open, flood with water for at least 15 minutes. If redness, burning, blurred vision, or swelling persist transport to nearest medical facility for additional treatment.

Skin: If skin contact occurs, remove contaminated clothing and wash skin thoroughly with water and follow by washing with soap if available.

Product: LINSEED OIL WITH ANTI-MOULD

Inhaled: Remove victim from exposure if safe to do so. If rapid recovery does not occur, transport to nearest medical facility for additional treatment. Remove contaminated clothing.

First Aid facilities: Potable water should be available to rinse eyes or skin. Provide eye baths and safety showers.

Advice to Doctor: Treat symptomatically.

Additional Information: None available.

SECTION 5 FIRE FIGHTING MEASURES

Suitable Extinguishing Media: Foam, water spray or fog, dry chemical powder. Do not use water in a jet.

Hazards from combustion products: Will float and can be reignited on surface water. Vapour is heavier than air, can spread along ground and distant ignition is possible.

Precautions for Fire Fighters and Special Protective Equipment: Wear full protective clothing and self-contained breathing apparatus.

Additional Information: Hazchem code – Not applicable.

SECTION 6 ACCIDENTAL RELEASE MEASURES

Observe all local and national regulations.

Spills and Disposal: Avoid contact with spilled or released material. Shut off leaks, if possible without personal risks. Remove all sources of ignition in the surrounding area. Use appropriate containment to avoid environmental contamination. Prevent from spreading and entering waterway using sand, earth or other appropriate barriers. Take precautionary measure against static discharge. Ensure electrical continuity by bonding and earthing all equipment.

Methods and Materials for Containment and Clean Up Procedures: For small spills (<1 drum), transfer by mechanical means to a labelled, sealable container for product recovery or safe disposal. Allow any residues to evaporate or use an appropriate absorbent material and dispose of safely. For larger spills (> 1 drum), transfer by means such as a vacuum truck to a salvage tank for recovery or disposal. Do not flush residues with water. Retain as contaminated waste. Allow any residues to evaporate or use an appropriate absorbent material and dispose of safely.

SECTION 7 HANDLING AND STORAGE

Precautions for Safe Handling and Storage: Avoid breathing of or contact with material. Use in well ventilated areas. Wash thoroughly after handling. Avoid contact with skin and eyes and clothing. Handle open containers in well ventilated area. Ensure that the workplace is ventilated such that the Occupational Exposure limit is not exceeded. Do not empty into drains. Do not eat, drink or smoke in contaminated areas. Before eating, drinking or smoking, remove contaminated clothing and wash hands. Do not store near strong oxidants.

Dispensing: Electrostatic charges may be generated during transfer. Electrostatic discharge may cause fire. Ensure electrical continuity by earthing all equipment.

Flammability: Combustible.

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Standards: In the absence of occupational exposure standards for this product, it is recommended that the following for Hydrocarbon is adopted. 350mg/m³ TWA (8hr).

Biological Limit Values: No biological limit allocated.

Personal Protective Equipment:

Respiratory Protection: If work practices do not maintain airborne level below the exposure standard, use appropriate respiratory protection equipment. When using respirators, select an appropriate combination of mask and filter and select a filter for organic gases and vapours (boiling point > 65 Deg C). Respirators should comply with AS1716 or an equivalent approved by a state/territory authority.

Hand Protection: Use solvent resistant gloves, nitrile for longer term protection or PVC and neoprene for incidental splashes.

Eye Protection: Wear safety goggles.

Protective Clothing: Use chemical resistant glove/gauntlets, boots and apron. Skin protection not ordinarily required beyond standard issue work clothes.

Engineering Controls: Ensure that adequate ventilation is provided. Maintain air concentrations below recommended exposure standards. Avoid generating and inhaling mists. Keep containers closed when not in use.

Product: LINSEED OIL WITH ANTI-MOULD

SECTION 9 IDENTIFICATION

PHYSICAL DESCRIPTION / CHEMICAL PROPERTIES

Appearance	Pale Golden liquid
Odour	Paraffinic/Characteristic
pH:	N/A
Vapour Pressure (kPa @ 20°C):	Data not available
Vapour Density (air = 1)	> 1
Boiling Point (°C):	Typical 195 - 250
Freezing/Melting Point (°C):	Data not available
Solubility in Water	Negligible
Specific Gravity (g/ml @ 15°C):	0.85
Flashpoint (°C):	Typical 75 (CC)
Flammability Limits (%):	0.6 - 7.0
Auto Ignition Temperature (°C):	> 200
Percent Volatiles	65

SECTION 10 STABILITY AND REACTIVITY

Chemical Stability: Stable under normal conditions of use.

Conditions to Avoid: Avoid heat, sparks, open flames and other ignition sources. Soak any soiled rags in water to avoid spontaneous combustion.

Incompatible Materials: Strong oxidising agents.

Hazardous Decomposition Products: Thermal decomposition is highly dependant on conditions. A complex mixture of airborne solids, liquids, gases, including carbon monoxide, carbon dioxide and other organic compounds will be evolved when this material undergoes combustion or thermal or oxidative degradation.

SECTION 11 TOXICOLOGICAL INFORMATION

HEALTH EFFECTS

Acute:

Swallowed: Expected to be of low toxicity: Aspiration into lungs when swallowed or vomited may cause chemical pneumonitis.

Eye: Expected to be non-irritating to eyes.

Skin: Prolonged contact may cause defatting of skin which can lead to dermatitis.

Inhaled: Inhalation of vapours or mists may cause irritation to the respiratory system.

Chronic: Central nervous system: repeated exposure affects the nervous system.

SECTION 12 ECOLOGICAL INFORMATION

Ecotoxicity:

Fish	: Harmful 10 < LC/EC/IC50 <= 100mg/l
Aquatic invertebrates	: Low toxicity: LC/EC/IC50 > 100mg/l
Algae	: Harmful 10 < LC/EC/IC50 <= 100mg/l
Microorganisms	: Expected to be Harmful 10 < LC/EC/IC50 <= 100mg/l

Mobility: Floats on water. Adsorbs to soil and has low mobility.

Persistence/degradability: Readily biodegradable. Degrades rapidly in air by photo-chemical means.

Bioaccumulation: Has the potential to bioaccumulate.

SECTION 13 DISPOSAL CONSIDERATIONS

Disposal Methods: Ensure waste disposal conforms to local waste disposal regulations.

SECTION 14 TRANSPORT INFORMATION

UN Number:	N/A	Proper Shipping Name:	N/A
Class:	N/A	Subsidiary Risk:	None allocated
Packing Group:	N/A	Hazchem Code:	N/A
Special Precautions for User:	None		

Product: LINSEED OIL WITH ANTI-MOULD

SECTION 15 REGULATORY INFORMATION

Poisons Schedule : 5

AICS : Listed

Dangerous Goods Initial Emergency Response Guide (SAA/SNZ HB76:2010) : None

SECTION 16 OTHER INFORMATION

Further Information may be obtained by contacting Recochem on (07) 3308 5200

The information sourced for the preparation of this document was correct and complete at the time of writing to the best of the writer's knowledge. The document represents the commitment to the company's responsibilities surrounding the supply of this product, undertaken in good faith. This document should be taken as a safety guide for the product and its recommended uses but is in no way an absolute authority. Please consult the relevant legislation and regulations governing the use and storage of this type of product.
