



SAFETY DATA SHEET

SECTION 1 IDENTIFICATION: PRODUCT IDENTIFIER AND CHEMICAL IDENTITY

Product Identifier	METHYL ISOBUTYL KETONE
Other Names	4-Methyl-2-Pentanone, Isopropyl Acetone
Manufacturer's Product Code	16772
Recommended Use	Solvent

Details of Supplier/Manufacturer

Company:	Recochem Inc. ABN: 69 010 485 999
Address:	1809 Lytton Road, Lytton, Queensland 4178
Phone:	(07) 3308 5200 Fax: (07) 3308 5201
Website:	www.recochem.com.au



Emergency Telephone Numbers

Business Hours:	(07) 3308 5200
After Hours:	1300 131 001
Poisons Information:	Australia: 13 11 26 New Zealand: 0800 764 766


SECTION 2 HAZARDS IDENTIFICATION

Hazardous chemical	<i>according to classification by Safe Work Australia</i>
Dangerous goods	<i>according to the Australian Code for the Transport of Dangerous Goods by Road and Rail</i>

Signal Word	DANGER
--------------------	---------------

GHS Classification	Pictogram	Hazard statement
Flammable Liquids, Category 2	 FLAME	H225 Highly flammable liquid and vapour
Carcinogenicity, Category 2	 HEALTH HAZARD	H351 Suspected of causing cancer

Product: METHYL ISOBUTYL KETONE

Serious Eye Damage/Irritation, Category 2A	 <p>EXCLAMATION MARK</p>	H319 Causes serious eye irritation
Acute Toxicity – Inhalation, Category 4		H332 Harmful if inhaled
Specific Target Organ Toxicity (Single exposure), Category 3		H335 May cause respiratory irritation
Non-GHS (Safe Work Australia)	N/A	AUH066 Repeated exposure may cause skin dryness or cracking

Precautionary statements:

<i>GENERAL</i>	
P101	If medical advice is needed, have product container or label at hand
P102	Keep out of reach of children
P103	Read label before use
<i>PREVENTATIVE</i>	
P201	Obtain special instructions before use
P202	Do not handle until all safety precautions have been read and understood
P210	Keep away from heat/sparks/open flames/hot surfaces. – No smoking
P233	Keep container tightly closed
P240	Ground/bond container and receiving equipment
P241	Use explosion-proof electrical/ventilation/lighting equipment
P242	Use only non-sparking tools
P243	Take precautionary measures against static discharge
P261	Avoid breathing mist/vapours/spray
P264	Wash thoroughly after handling
P271	Use only outdoors or in a well-ventilated area
P280	Wear protective gloves/eye protection/face protection
P281	Use personal protective equipment as required
<i>RESPONSE</i>	
P303 + P361 + P353	IF ON SKIN (or hair): Take off contaminated clothing and wash before reuse. Rinse skin with water/shower
P304 + P340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P308 + P313	IF exposed or concerned: Get medical advice/attention
P312	Call a POISON CENTER or doctor/physician if you feel unwell
P337 + P313	If eye irritation persists: Get medical advice/attention
P370 + P378	In case of fire: Use foam/water spray/fog for extinction
<i>STORAGE</i>	
P403 + P233	Store in a well-ventilated place. Keep container tightly closed
P403 + P235	Store in a well-ventilated place. Keep cool
P405	Store locked up
<i>DISPOSAL</i>	
P501	Dispose of contents/container in accordance with local regulations

SECTION 3 COMPOSITION AND INFORMATION ON INGREDIENTS

Ingredients Names and Proportions

Chemical Entity	CAS Number	Proportion (%)
Methyl Isobutyl Ketone	108-10-1	> 99

SECTION 4 FIRST AID MEASURES

Description of necessary first aid measures

Inhalation:	Remove victim from exposure if safe to do so. If rapid recovery does not occur, transport to nearest medical facility for additional treatment. Remove contaminated clothing.
Skin Contact:	If skin contact occurs, remove contaminated clothing and wash skin thoroughly with water and follow by washing with soap if available. If irritation occurs seek medical advice.
Eye Contact:	If in eyes, hold eyes open, flood with water for at least 15 minutes. Seek immediate medical assistance.
Ingestion:	If swallowed, do NOT induce vomiting. Seek medical advice.

Symptoms caused by exposure

Inhalation:	May cause irritation.
Skin:	May cause irritation – dryness and itching.
Eye:	Irritant - redness and swelling.
Ingestion:	Swallowing may result in irritation of the gastrointestinal tract, nausea, headache and vomiting

Medical attention and special treatment

Treat symptomatically.

SECTION 5 FIRE FIGHTING MEASURES

Suitable extinguishing equipment

Use water fog or spray, foam, dry agent.

Specific hazards arising from the chemical

Highly flammable liquid. May form flammable vapour mixture with air. Avoid all ignition sources. Flameproof equipment necessary in area where chemical is being used. Nearby equipment must be earthed. Vapours may travel considerable distances to source of ignition and flashback. Vapours may accumulate in low or confined areas. Combustion products may include carbon monoxide and/or carbon dioxide.

Special protective equipment and precautions for fire fighters

Wear full protective clothing and self-contained breathing apparatus. Heating can cause expansion or decomposition leading to violent rupture of containers. Hazchem code ●3YE.

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Avoid contact with spilled or released material. Shut off leaks, if possible without personal risks. Isolate hazard area and deny entry to unnecessary or unprotected personnel. Remove all sources of ignition in the surrounding area. Take precautionary measure against static discharge. Use non-sparking tools. Ensure electrical continuity by bonding and earthing all equipment.

Environmental precautions

Prevent spills from entering drains or waterways. Use appropriate containment to avoid environmental contamination.

Product: METHYL ISOBUTYL KETONE

Methods and materials for containment and cleaning up

For small spills (< 1 drum), transfer by mechanical means to a labelled, sealable container for product recovery or safe disposal. Allow any residues to evaporate or use an appropriate absorbent material and dispose of safely.

For larger spills (> 1 drum), transfer by means such as a vacuum truck to a salvage tank for recovery or disposal. Retain as contaminated waste. Allow any residues to evaporate or use an appropriate absorbent material and dispose of safely.

SECTION 7 HANDLING AND STORAGE

Precautions for safe handling

Highly flammable product. Avoid breathing vapours. Avoid contact with skin, eyes and clothing. Handle and open containers with care in a well-ventilated area. Ensure that the workplace is ventilated such that the Occupational Exposure limit is not exceeded. Wash thoroughly after handling. Do not eat, drink or smoke in contaminated areas. Electrostatic charges may be generated during transfer. Electrostatic discharge may cause fire. Ensure electrical continuity by earthing all equipment. Do not empty into drains.

Conditions for safe storage, including any incompatibilities

Store in a well-ventilated area, away from sunlight, ignition sources and other sources of heat. Do not store near strong oxidisers and alkalis.

SECTION 8 EXPOSURE CONTROLS AND PERSONAL PROTECTION

Exposure control measures

From National Occupational Health & Safety Commission (NOHSC) Worksafe Australia - Methyl Isobutyl Ketone: 205mg/m³ (50ppm) TWA (8hr), STEL 307mg/m³ (75ppm)

Biological monitoring

No biological limit allocated.

Engineering controls

Ensure that adequate ventilation is provided. Maintain air concentrations below recommended exposure standards. Avoid generating and inhaling mists and vapours. Keep containers closed when not in use.

Individual protection measures

Eye and face protection:	Wear safety goggles.
Skin protection:	Use solvent resistant gloves, nitrile for longer term protection or PVC and neoprene for incidental splashes.
Respiratory protection:	If work practices do not maintain airborne level below the exposure standard, use appropriate respiratory protection equipment. When using respirators, select an appropriate combination of mask and filter. Select a filter for organic gases and vapours (boiling point > 65°C). Respirators should comply with AS1716 or an equivalent approved by a state/territory authority.
Thermal hazards:	Not applicable.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Colourless clear liquid
Odour:	Mild
Odour threshold (ppm):	Data not available
pH:	Data not available
Melting point/freezing point (°C):	-84
Initial boiling point and boiling range (°C):	114

Product: METHYL ISOBUTYL KETONE

Flash point (°C):	16 (closed cup)
Evaporation rate (Butyl acetate = 1):	Data not available
Flammability:	Highly flammable
Upper/lower flammability or explosive limits (%):	1.2 – 8.0
Vapour pressure (mmHg @ 20°C):	15.0
Vapour density (air = 1, @ 15°C):	3.5
Density (g/ml @ 15°C):	0.802
Solubility (g/L):	20
Partition coefficient: n-octanol/water:	Data not available
Auto-ignition temperature (°C):	460
Decomposition temperature (°C):	Data not available
Kinematic viscosity (mm ² /s @ 20°C):	Data not available

SECTION 10 STABILITY AND REACTIVITY**Reactivity**

Stable under normal conditions of use.

Chemical stability

Stable under normal conditions of use.

Possibility of hazardous reactions

Stable under normal conditions of use.

Conditions to avoid

Avoid heat, sparks, open flames and other ignition sources.

Incompatible materials

Strong oxidising agents, alkalis.

Hazardous decomposition products

Burning can produce carbon monoxide and/or carbon dioxide.

SECTION 11 TOXICOLOGICAL INFORMATION

Acute toxicity:	Inhalation LC50 (rat): 8.2 – 16.4mg/m ³ /4hours Oral LD50 (rat, mouse) > 2000mg/kg Dermal LD50 (rabbit) > 20,000mg/kg
Skin corrosion/irritation:	Contact with skin may result in irritation. Will have a degreasing effect on the skin. Prolonged exposure can cause dermatitis.
Serious eye damage/irritation:	Irritating to eyes.
Respiratory or skin sensitisation:	Not expected to be a sensitiser.
Germ cell mutagenicity:	Not expected to be mutagenic.
Carcinogenicity:	Classified by the International Agency for Research on Cancer (IARC) as a Group 2B. Group 2B – The agent is possibly carcinogenic to humans.
Reproductive toxicity:	Not expected to impair fertility.

Product: METHYL ISOBUTYL KETONE

Specific Target Organ Toxicity (STOT) – single exposure:	Breathing in vapour may produce irritation.
Specific Target Organ Toxicity (STOT) – repeated exposure:	No data available.
Aspiration hazard:	No data available.

SECTION 12 ECOLOGICAL INFORMATION

Ecotoxicity

Acute toxicity:

Fish –	Data not available
Aquatic invertebrate –	Data not available
Algae –	Data not available
Microorganisms –	Data not available

Chronic toxicity:

Fish –	Data not available
Aquatic invertebrate –	Data not available
Algae –	Data not available
Microorganisms –	Data not available

Persistence and degradability

Biodegradable; bioaccumulation is not expected.

Bioaccumulative potential

Data not available.

Mobility in soil

Highly mobile and may leach into to ground water.

Other adverse effects

Data not available.

SECTION 13 DISPOSAL CONSIDERATIONS

Ensure waste disposal conforms to local waste disposal regulations.

SECTION 14 TRANSPORT INFORMATION

UN number:	1245
Proper shipping name:	Methyl Isobutyl Ketone
Australian Dangerous Goods class:	3
Australian Dangerous Goods packing group:	II
Hazchem code:	●3YE

SECTION 15 REGULATORY INFORMATION

Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP), Poisons Schedule:	5
Australian Inventory of Chemical Substances (AICS):	Listed
Dangerous Goods Initial Emergency Response Guide (SAA/SNZ HB76):	14

SECTION 16 OTHER INFORMATION

Date of preparation:	31/01/2017
Revision number:	5
Changes in this revision:	Update to hazard classification

This SDS summarises product safety information at the date of issue, to the best of our knowledge, as a general guide. Recochem cannot anticipate or control the conditions under which the product is used, so prior to usage each user must assess and control the risks associated with their use of the product. Users should also consult the relevant legislation governing the use and storage of this product. We make no warranties, express or implied, and assume no liability in connection with any use of information contained within this document. If clarification or further information is needed, the user should contact Recochem on (07) 3308 5200.
