



VISCOSITY IMPROVERS

Polyisobutylene

DESCRIPTION

A range of liquid polymers based on the Isobutene monomer for use in lubricants, greases and specialty chemical formulations.

FEATURES

The **Polyisobutylene** range is very stable and provides consistent viscosity index improvement to lubricating oils.

PACKAGING

The **Polyisobutylene** range is available in IBCs (1000 litre bulk containers) and 200 litre drums.

SAFETY

Please consult the MSDS on **Polyisobutylene** before use.

The information and recommendations contained herein are based on data believed to be correct at this time. However, no guarantee of any kind, expressed or implied is made with respect to the information contained herein.

Typical Characteristics

Polyisobutylene 2400
 Molecular Mass 2400Ave
 Flash Point.....>165°C
 Specific Gravity.....0.89
 Viscosity@100°C..... 4300cSt

 **MSDS** available

Typical Characteristics

Polyisobutylene 950
 Molecular Mass 950Ave
 Flash Point.....>165°C
 Specific Gravity.....0.89
 Viscosity@100°C.....230cSt

 **MSDS** available

Typical Characteristics

Polyisobutylene 450
 Molecular Mass 450Ave
 Flash Point.....>150°C
 Specific Gravity.....0.85
 Viscosity@100°C..... 14cSt
 Pour Point..... -30°C

 **MSDS** available

QUEENSLAND
Tel +61 7 3308 5200
Fax +61 7 3308 5201

NEW SOUTH WALES
Tel +61 2 8709 9600
Fax +61 2 9791 5066

VICTORIA
Tel +61 3 9408 4144
Fax +61 3 9408 4155

SOUTH AUSTRALIA
Tel +61 8 8222 1333
Fax +61 8 8260 7883

WESTERN AUSTRALIA
Tel +61 8 9352 3000
Fax +61 8 9352 3033