



# SAFETY DATA SHEET

## SECTION 1 IDENTIFICATION: PRODUCT IDENTIFIER AND CHEMICAL IDENTITY

<b>Product Identifier</b>	<b>WHITE SPIRIT</b>
<b>Other Names</b>	Turpentine substitute, Stoddards Solvent, LAWS
<b>Manufacturer's Product Code</b>	16004
<b>Recommended Use</b>	Solvent, dry cleaning fluid

### Details of Supplier/Manufacturer

Company:	Recochem Inc. ABN: 69 010 485 999
Address:	1809 Lytton Road, Lytton, Queensland 4178, Australia
Phone:	+617 3308 5200 Fax: +617 3308 5201
Website:	www.recochem.com.au

### Details of Distributor

Company:	Owens Logistics
Address:	3-5 Kahu Street, Otahuhu, Auckland
Phone:	(09) 270 1310 Fax: (09) 270 1311



### Emergency Telephone Numbers

Poisons Information:	0800 764 766
----------------------	--------------



## SECTION 2 HAZARDS IDENTIFICATION

<b>Hazardous chemical</b>	<i>according to classification by Safe Work Australia</i>
<b>Dangerous goods</b>	<i>according to the Australian Code for the Transport of Dangerous Goods by Road and Rail</i>

<b>Signal Word</b>	<b>DANGER</b>
--------------------	---------------

GHS Classification	Pictogram	Hazard statement
Flammable Liquids, Category 3	 FLAME	H226 Flammable liquid and vapour
Aspiration Hazard, Category 1	 HEALTH HAZARD	H304 May be fatal if swallowed and enters airways
Specific Target Organ Toxicity (Repeated exposure), Category 1		H372 Causes damage to organs (central nervous system) through prolonged or repeated exposure

**Product: WHITE SPIRIT**

Skin Corrosion/Irritation, Category 2	 EXCLAMATION MARK	H315 Causes skin irritation
Specific Target Organ Toxicity (Single exposure), Category 3		H335 May cause respiratory irritation H336 May cause drowsiness or dizziness
Chronic Aquatic Toxicity, Category 2	 ENVIRONMENTAL HAZARD	H411 Toxic to aquatic life with long lasting effects

**Precautionary statements:**

<i>GENERAL</i>	
P101	If medical advice is needed, have product container or label at hand
P102	Keep out of reach of children
P103	Read label before use
<i>PREVENTATIVE</i>	
P210	Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking
P233	Keep container tightly closed
P240	Ground and bond container and receiving equipment
P241	Use explosion-proof electrical/ventilation/lighting equipment
P242	Use non-sparking tools
P243	Take action to prevent static discharge
P260	Do not breathe mist/vapours/spray
P261	Avoid breathing mist/vapours/spray
P264	Wash thoroughly after handling
P270	Do not eat, drink or smoke when using this product
P271	Use only outdoors or in a well-ventilated area
P273	Avoid release to the environment
P280	Wear protective gloves/eye protection/face protection
<i>RESPONSE</i>	
P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
P302 + P352	IF ON SKIN: Wash with plenty of soap and water
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing
P312	Call a POISON CENTER or doctor/physician if you feel unwell
P314	Get medical advice/attention if you feel unwell
P331	Do NOT induce vomiting
P332 + P313	If skin irritation occurs: Get medical advice/attention
P362 + P364	Take off contaminated clothing and wash it before reuse
P370 + P378	In case of fire: Use foam/water spray/fog to extinguish
P391	Collect spillage
<i>STORAGE</i>	
P403 + P233	Store in a well-ventilated place. Keep container tightly closed
P403 + P235	Store in a well-ventilated place. Keep cool
P405	Store locked up

**Product: WHITE SPIRIT**

<i>DISPOSAL</i>	P501	Dispose of contents/container in accordance with local regulations
-----------------	------	--

**SECTION 3 COMPOSITION AND INFORMATION ON INGREDIENTS****Ingredients Names and Proportions**

Chemical Entity	CAS Number	Proportion (%)
Naphtha (petroleum), hydrodesulphurized heavy (Low Aromatic White Spirit)	64742-82-1	100
With components:		
1,2,4-Trimethylbenzene	95-63-6	< 10
1,3,5-Trimethylbenzene	108-67-8	< 10
Xylene, Mixed Isomers	1330-20-7	< 10
Note – contains < 0.1% benzene		

**SECTION 4 FIRST AID MEASURES****Description of necessary first aid measures**

Inhalation:	Keep victim calm and remove to fresh air if safe to do so. If rapid recovery does not occur, transport to nearest medical facility for additional treatment.
Skin Contact:	If skin contact occurs, remove contaminated clothing and wash skin thoroughly with water and follow by washing with soap if available.
Eye Contact:	If in eyes, hold eyes open, flood with water for at least 15 minutes. If irritation persists seek medical attention.
Ingestion:	If swallowed, do NOT induce vomiting. Transport to nearest medical facility for additional treatment. If vomiting occurs spontaneously, keep head below hips to prevent aspiration.

**Symptoms caused by exposure**

Inhalation:	Breathing of high vapour concentrations may cause central nervous system depression resulting in dizziness, light-headedness, headache, nausea and loss of coordination. Continuous inhalation may result in unconsciousness and death.
Skin:	May include redness and cracking.
Eye:	May include redness and swelling.
Ingestion:	May include headache, nausea, coughing and shortness of breath.

**Medical attention and special treatment**

Treat symptomatically.

**SECTION 5 FIRE FIGHTING MEASURES****Suitable extinguishing equipment**

Foam, water spray or fog, dry chemical powder or carbon dioxide. Do not use water in a jet.

**Specific hazards arising from the chemical**

Carbon monoxide may be evolved if incomplete combustion occurs. Will float and can be reignited on surface water. Vapour is heavier than air, can spread along ground and distant ignition is possible.

**Special protective equipment and precautions for fire fighters**

Wear full protective clothing and self-contained breathing apparatus. Hazchem code 3Y.

**SECTION 6 ACCIDENTAL RELEASE MEASURES****Personal precautions, protective equipment and emergency procedures**

Avoid contact with spilled or released material. Shut off leaks, if possible without personal risks. Isolate hazard area and deny entry to unnecessary or unprotected personnel. Remove all sources of ignition in the

**Product: WHITE SPIRIT**

surrounding area. Take precautionary measure against static discharge. Ensure electrical continuity by bonding and earthing all equipment.

**Environmental precautions**

Use appropriate containment to avoid environmental contamination. Prevent from spreading and entering waterway using sand, earth or other appropriate barriers. Attempt to disperse the vapour or to direct its flow to a safe location for example by using fog sprays. Ventilate contaminated area thoroughly.

**Methods and materials for containment and cleaning up**

For small spills (< 1 drum), transfer by mechanical means to a labelled, sealable container for product recovery or safe disposal. Allow any residues to evaporate or use an appropriate absorbent material and dispose of safely.

For larger spills (> 1 drum), transfer by means such as a vacuum truck to a salvage tank for recovery or disposal. Do not flush residues with water. Retain as contaminated waste. Allow any residues to evaporate or use an appropriate absorbent material and dispose of safely.

---

**SECTION 7 HANDLING AND STORAGE**

---

**Precautions for safe handling**

Flammable product. Avoid breathing vapours. Handle and open containers with care in a well-ventilated area. Ensure that the workplace is ventilated such that the Occupational Exposure limit is not exceeded. Avoid contact with skin, eyes and clothing. Wash thoroughly after handling. Do not eat, drink or smoke in contaminated areas. Electrostatic charges may be generated during transfer. Electrostatic discharge may cause fire. Ensure electrical continuity by earthing all equipment. Flameproof equipment necessary in area where chemical is being used. Vapours may accumulate in low or confined areas.

**Conditions for safe storage, including any incompatibilities**

Bulk storage tanks should be bunded. Store in a well-ventilated area, away from sunlight, ignition sources and other sources of heat. Do not store near strong oxidants.

---

**SECTION 8 EXPOSURE CONTROLS AND PERSONAL PROTECTION**

---

**Exposure control measures**

In the absence of data from National Occupational Health & Safety Commission (NOHSC) Worksafe Australia use -  
Mineral Spirits 150-200 HSPA: 350mg/m<sup>3</sup> TWA (8hr)

**Biological monitoring**

No biological limit allocated.

**Engineering controls**

Ensure that adequate ventilation is provided. Maintain air concentrations below recommended exposure standards. Avoid generating and inhaling mists and vapours. Keep containers closed when not in use.

**Individual protection measures**

Eye and face protection:	Wear safety goggles.
Skin protection:	Use solvent resistant gloves, nitrile for longer term protection or PVC and neoprene for incidental splashes.
Respiratory protection:	If work practices do not maintain airborne level below the exposure standard, use appropriate respiratory protection equipment. When using respirators, select an appropriate combination of mask and filter. Select a filter for organic gases and vapours (boiling point > 65°C). Respirators should comply with AS1716 or an equivalent approved by a state/territory authority.
Thermal hazards:	Not applicable.

**SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES**

Appearance:	Colourless liquid
Odour:	Paraffinic
Odour threshold (ppm):	Data not available
pH:	Data not available
Melting point/freezing point (°C):	Data not available
Initial boiling point and boiling range (°C):	149 - 194
Flash point (°C):	42 (Abel)
Evaporation rate (Butyl acetate = 1):	Data not available
Flammability:	Flammable
Upper/lower flammability or explosive limits (%):	0.7 - 6.5
Vapour pressure (kPa @ 20°C):	Typical 0.37
Vapour density (air = 1 @ 15°C):	4.35
Density (g/ml @ 15°C):	0.78
Solubility (kg/m <sup>3</sup> ):	Not miscible with water
Partition coefficient: n-octanol/water:	Data not available
Auto-ignition temperature (°C):	Typical 296 (ASTM E-659)
Decomposition temperature (°C):	Data not available
Kinematic viscosity (mm <sup>2</sup> /s @ 25°C):	Typical 1.08

**SECTION 10 STABILITY AND REACTIVITY**

**Reactivity**

Stable under normal conditions of use.

**Chemical stability**

Stable under normal conditions of use.

**Possibility of hazardous reactions**

Stable under normal conditions of use.

**Conditions to avoid**

Avoid heat, sparks, open flames and other ignition sources.

**Incompatible materials**

Strong oxidising agents.

**Hazardous decomposition products**

Thermal decomposition is highly dependent on conditions. A complex mixture of airborne solids, liquids, gases, including carbon monoxide, carbon dioxide and other organic compounds will be evolved when this material undergoes combustion or thermal or oxidative degradation.

**SECTION 11 TOXICOLOGICAL INFORMATION**

Acute toxicity:	Expected to be of low toxicity - LD50 Oral (rat) > 2000 mg/kg
-----------------	--

**Product: WHITE SPIRIT**

	LC50 Inhalation greater than near-saturated vapour concentration (rat, 4h) LD50 Dermal (rabbit) > 2000 mg/kg
Skin corrosion/irritation:	Irritant. Prolonged contact may cause defatting of skin which can lead to dermatitis.
Serious eye damage/irritation:	Mild irritant.
Respiratory or skin sensitisation:	Not expected to be a sensitiser.
Germ cell mutagenicity:	Not expected to be mutagenic.
Carcinogenicity:	Not expected to be carcinogenic.
Reproductive toxicity:	Not expected to impair fertility.
Specific Target Organ Toxicity (STOT) – single exposure:	Inhalation of vapours or mists may cause irritation to the respiratory system.
Specific Target Organ Toxicity (STOT) – repeated exposure:	Central nervous system: repeated exposure affects the nervous system. Effects seen at high doses only. Auditory system: prolonged and repeated exposures to high concentrations have resulted in hearing loss in rats. Solvent abuse and noise interaction in the work environment may cause hearing loss.
Aspiration hazard:	Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.

**SECTION 12 ECOLOGICAL INFORMATION****Ecotoxicity**

Acute toxicity:

Fish –	Expected to be harmful: 10 < LC/EC/IC50 <= 100mg/l
Aquatic invertebrate –	Expected to be harmful: 10 < LC/EC/IC50 <= 100mg/l
Algae –	Expected to be harmful: 10 < LC/EC/IC50 <= 100mg/l
Microorganisms –	Expected to be harmful: 10 < LC/EC/IC50 <= 100mg/l

Chronic toxicity:

Fish –	Data not available
Aquatic invertebrate –	Data not available
Algae –	Data not available
Microorganisms –	Data not available

**Persistence and degradability**

Readily biodegradable. Oxidises by photo-chemical reactions in air.

**Bioaccumulative potential**

Has the potential to bioaccumulate.

**Mobility in soil**

Floats on water.

**Other adverse effects**

Data not available.

**Product: WHITE SPIRIT**

---

**SECTION 13 DISPOSAL CONSIDERATIONS**

---

Ensure waste disposal conforms to local waste disposal regulations.

---

**SECTION 14 TRANSPORT INFORMATION**

---

<b>UN number:</b>	1300
<b>Proper shipping name:</b>	Turpentine Substitute
<b>Australian Dangerous Goods class:</b>	3
<b>Australian Dangerous Goods packing group:</b>	III
<b>Hazchem code:</b>	3Y

---

**SECTION 15 REGULATORY INFORMATION**

---

Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP), Poisons Schedule:	5
Australian Inventory of Chemical Substances (AICS):	Listed
Dangerous Goods Initial Emergency Response Guide (SAA/SNZ HB76):	14
New Zealand HSNO, Classification:	Solvents (Flammable) Group Standard Classification - 3.1C, 6.1E, 6.3B, 9.1B

---

**SECTION 16 OTHER INFORMATION**

---

<b>Date of preparation:</b>	28/02/2022
<b>Revision number:</b>	4
<b>Changes in this revision:</b>	Reviewed due to expiration

---

This SDS summarises product safety information at the date of issue, to the best of our knowledge, as a general guide. Recochem cannot anticipate or control the conditions under which the product is used, so prior to usage each user must assess and control the risks associated with their use of the product. Users should also consult the relevant legislation governing the use and storage of this product. We make no warranties, express or implied, and assume no liability in connection with any use of information contained within this document. If clarification or further information is needed, the user should contact Recochem on +617 3308 5200.

---