



SOLVENTS / PENETRANTS

# Recosol 80/100

## DESCRIPTION

A highly refined petroleum solvent specifically developed for the preparation of metallic surfaces prior to painting and in particular powder coatings. **Recosol 80/100** removes most surface contaminants easily and evaporates very quickly after cleaning.

## FEATURES

A clear and bright fluid which leaves no stains, residue or lasting odour.

A high purity product which contains almost no aromatics.

**High Purity** – **Recosol 80/100** is a narrow boiling range solvent. It does not contain any appreciable levels of aromatic compounds, rendering surfaces clean and dry in a short time.

**Odour and Colour** – **Recosol 80/100** is water white and has a mild odour, especially in comparison with other solvents traditionally used for surface preparation prior to painting.

## PACKAGING

**Recosol 80/100** is available in drums.

## SAFETY

Please consult the MSDS on **Recosol 80/100** before use.

The information and recommendations contained herein are based on data believed to be correct at this time. However, no guarantee of any kind, expressed or implied is made with respect to the information contained herein.

### Typical Characteristics

Specific Gravity.....	0.716
Flash Point (open cup).....	-9°C
Boiling Range .....	79-96°C
Percent Volatiles .....	100%
Aromatics.....	0.05%



MSDS available

QUEENSLAND  
Tel +61 7 3308 5200  
Fax +61 7 3308 5201

NEW SOUTH WALES  
Tel +61 2 8709 9600  
Fax +61 2 9791 5066

VICTORIA  
Tel +61 3 9408 4144  
Fax +61 3 9408 4155

SOUTH AUSTRALIA  
Tel +61 8 8222 1333  
Fax +61 8 8260 7883

WESTERN AUSTRALIA  
Tel +61 8 9352 3000  
Fax +61 8 9352 3033